





TO IPS

Amenity Range / IP Bulkhead (Square)

A range of low energy bulkhead luminaires suitable for interior and exterior use.

Specification

- Injection moulded polycarbonate body
- Injection moulded polycarbonate prismatic lens
- U.V. stabilised to prevent discolouring
- · Suitable for wall or ceiling mounting
- · Removable gear tray for easy maintenance
- LED 4000°K

Application

- Stairwells
- Perimeter lighting
- · Schools / Colleges etc
- Corridors
- Toilets
- Canopy

















Product Codes

| | T0IPS28DZBP T0IPS28DZWP | Square Black + Prism. Dif Square White + Prism. Dif | 28W 2D 28W 2D | |
|--------------|--|--|------------------|--------|
| LED | T0IPS1500EZBP | Square Black + Prism. Dif | 12W | 1500Lm |
| LED | TT0IPS1500EZWP | Square White + Prism. Dif | 12W | 1500Lm |
| EM A | Add suffix /EM for 3hr Maintained Emergency | | | |
| IMPROVEMENTS | Wattage consumption and performance is subject to improvements. Please check the current technical data at the time of purchase. | | | |

Dimensions





www.brightfuturelighting.co.uk

Telephone: 0844 335 1021 Fax: 01905 620776 Email: sales@brightfuturelighting.co.uk