



T6 CDD

Recessed LED Range / Concealed Grid with Ribbed Diffuser



The flagship range of our recessed luminaire is designed to suit today's growing demands of lighting criteria.

Specification

- · Fabricated steel body
- Injection moulded end cap
- Suitable for 15-25mm exposed T grid ceiling
- · Suitable for plasterboard ceiling (see optional extra)
- Injection moulded polycarbonate body
- UV stabilised
- · Ribbed diffuser

Application

- · Reception
- · Call Centre
- · Circulation Area

- Offices
- Shops
- · Conference Room






















Product Codes

T6CDD155PZ	1 x 55W PLL
T6CDD255PZ	2 x 55W PLI
T6CDD214FZ	2 x 14W T5
T6CDD314FZ	3 x 14W T5
T6CDD414FZ	4 x 14W T5
T6CDD224FZ	2 x 24W T5
T6CDD324FZ	3 x 24W T5
T6CDD424FZ	4 x 24W T5




EM Add suffix /EM for 3hr Maintained Emergency




Optional Extras

OEM-ATT-01 T6CDXSB OEM-CDX-ECS

Dimensions



Plasterboard Recessing Kit Surface Conversion Box Chrome End Cap



www.brightfuturelighting.co.uk

Email: sales@brightfuturelighting.co.uk Fax: 01905 620776 Telephone: 0844 335 1021