



T6 IDD

Recessed Fluorescent / LED Range / Indirect with Prismatic Diffuser



www.brightfuturelighting.co.uk

Telephone: 0844 335 1021

Fax: 01905 620776

Email: sales@brightfuturelighting.co.uk

T6 IDD

Recessed Fluorescent / LED Range / Indirect with Prismatic Diffuser



Direct / Indirect recessed fluorescent / LED luminaire with centrally mounted opal and prismatic diffuser.

Specification

- Fabricated steel body
- Suitable for 15-25mm exposed T grid ceiling
- Suitable for plasterboard ceiling (see optional extra)
- Powder coated finish
- Opal and prismatic diffuser
- LED 4000°K

Application

- Reception
- Offices
- Call Centre
- Shops
- Conference Room



Product Codes

T6IDD155PZ	1 x 55W PLL
T6IDD255PZ	2 x 55W PLL
T6IDD240PZ	2 x 40W PLL
T6IDD214FZ	2 x 14W T5
T6IDD224FZ	2 x 24W T5

LED	T6IDD4520EZ	38W	4520Lm
------------	-------------	-----	--------

EM	Add suffix /EM for 3hr Maintained Emergency		
-----------	---	--	--

IMPROVEMENTS	Wattage consumption and performance is subject to improvements. Please check the current technical data at the time of purchase.		
---------------------	--	--	--

Optional Extras

OEM-ATT-01	Plasterboard Recessing Kit
OEM-ATT-05	Surface Conversion Box
OEM-ATT-11	Side Support Brackets - 4

Dimensions

