

Recessed LED Range / Recessed Square Round

www.brightfuturelighting.co.uk

T6 RSH

Bright Future Lightin

Recessed Range / Recessed Square Round

A slimline circular luminaire designed for 600mm x 600mm t-grid ceiling, with a selection of coloured filters available.

Specification

- Injection moulded polycarbonated opal diffuser
- Injection moulded polycarbonate base
- U.V. stabilised to prevent discolouring
- Fabricated steel body
- · Powder coated finish
- LED 4000°K

Application

CorridorsReception

Circulation AreaMedical Center




	30		EMERGENCY	œ	
	Product Codes				
	T6RSH28DZWO		28W 2D		
	T6RSH38DZWO		38W 2D		
	T6RSH40KZWO		40W T5	Circular	
LED	T6RSH1700EZWO		11W		1700 Lm
LED	T6RSH3150EZWO		22W		3150 Lm
LED	T6RSH3900EZWO		30W		3900 Lm
EMA	Add suffix /EM for 3hr Maintained Emergency				
MPROVEMENTS	Wattage consumption and performance is subject to improvements. Please check the current technical data at the time of purchase.				

Optional Extras OEM-ATT-01 T6CDXSB

Plasterboard Recessing Kit Surface Conversion Box

Dimensions



ww.brightfuturelighting.co.uk

Telephone: 0844 335 1021

Fax: 01905 620776

Email: sales@brightfuturelighting.co.uk