

Product data sheet



Chyme® Cylo Pendant










LED	7W	LED	Micro	PN 1166	LED	07	+	504
7W	LED	Midi	PN 1168	LED	07	+	506	
7W	LED	Maxi	PN 1170	LED	07	+	508	

3 Warm White LED (3000K)	CRI 80 7W
Lumen Output	1091 lm
LOR	0.63
CRI	80
Total Power	7.5W
Power Factor	0.95
Running Current	0.03A
Inrush Current	21.0A (126us)
Efficacy	91 lm/W
Emergency Output (BLF)	N/A

Chyme® Accent Pendant










LED									
7W	LED	Micro	PN 1172	LED	07	—	+	504	
7W	LED	Midi	PN 1174	—	07	—	+	506	
7W	LED	Maxi	PN 1176	LED	07	—	+	508	

4 Neutral White LED (4000K)	CRI 80 7W
Lumen Output	1137 lm
LOR	0.63
CRI	80
Total Power	7.5W
Power Factor	0.95
Running Current	0.03A
Inrush Current	21.0A (126us)
Efficacy	95 lm/W
Emergency Output (BLF)	N/A

- Slim, contemporary LED Pendant available in a choice of 3 lengths and 2 design options
- Available in a choice of lumen outputs, delivering up to 1137 lumens
- Efficacies of up to 95 lm/W
- Single point Zhaga Book 3 LED
- Life expectancy in excess of 51,000 hours (L80 B10)
- Colour stability within 3 MacAdams
- A range of specialist finishes available on request.
Pearl Copper, Gentian Blue and Anodic Malachite shown above

Gear type F & G must be operated through a DSI

- A Integral Driver
- F Digital Dim
- J Switch Dim
- S DALI Dim

3 Warm (3000K) 4 Neutral (4000K)

1 White (RAL 9010) 2 Urban Graphite (RAL 7046) 3 Black (RAL 9005)


561 5m Suspension (wire only)

562 Connector Housing



562 Connector Housing

Photometrics



504, 506, 508 DLOR: 0.63