

EMERGENCY DOWNLIGHT

supplying over three hours of non-maintained emergency lighting.







The Emergency Downlight is a standalone complement to any office or retail environment. The unit is discreet and unobtrusive when installed but capable of

IP Rating IP20 Weight (kg) 0.33 Dimensions (mm) 42 x 26 Bezel Battery 140 x 29 150 x 30 x 29 Driver





 Offices Corridors

Cut Out



trim as standard.

PART NO.	WATTAGE	DESCRIPTION	BEAM	EFFICACY	LUMENS	Ra/CCT	SYSTEM POWER
EMG013	3W	3W LED Emergency Downlight	120°	51	155	760	3W

Emergency Lighting Spacing

ESCAPE ROUTE 2M WIDE (1 LUX MIN)









PART NO.	MOUNTING HEIGHT (m)	TRANSERVE TO WALL	TRANSVERSE TO TRANSVERSE	AXIAL TO WALL	AXIAL TO AXIAL
EMG013	2.5	3.9	8.6	3.9	8.6
	4	4	9.8	4	9.8
	6	-	*·	-	

OPEN (ANTI-PANIC) AREA (0.5 LUX MIN)









PART NO.	MOUNTING HEIGHT (m)	TRANSERVE TO WALL	TRANSVERSE TO TRANSVERSE	AXIAL TO WALL	AXIAL TO AXIAL
EMG013	2.5	3.6	8.3	3.6	8.3
	4	4.1	10.9	4.1	10.9
	6	4	12.8	4	12.8