



Bright Future LED Product data sheet

T3ANIP3150EZ

Compact Decorative Range/Anti Ligature IP65

Product Codes

LED	T3ANIP3150EZ	22W	ø432mm	3150lm
------------	--------------	-----	--------	--------

Emergency

EM	T3ANIP13150EZ/EM	22W	ø432mm	3150lm
-----------	------------------	-----	--------	--------

DALI

WALL	T3ANIP3150XD	22W	ø432mm	3150lm
-------------	--------------	-----	--------	--------



* with IP65 seal kit

Material and Finish

- Injection moulded polycarbonate opal diffuser
- Powder coated finish
- Spun aluminium housing
- U.V. stabilised to prevent discolouring
- Tamper proof screws
- Anti-ligature

LED Characteristics

CCT	4000°K
Ra (CRI)	>80
Life expectancy	50,000 hrs L80 B10
Board lumens	3150lm
Rated power	22W

Electrical Input



Rated input voltage	~230-240V AC
Rated input frequency	50-60Hz
Power factor	>0.9
Running current	0.12A
Total wattage	25W

Photometric Data

Calculation file	T3ANIP3150EZ.ltd
LOR	99.98%
Luminaire lumens	2102.9lm
Efficacy LL/CW	84



Dimensions



Weight

