



# Bright Future LED Product data sheet

# T7GLA0750EXT

LED Recessed Downlighter


Product Codes				
<b>LED</b>	T7GLA0750EXT	ø80mm	8W	750lm
Emergency				
<b>EM</b>	T7GLA0750EXT/EM	ø80mm	8W	750lm
DALI				
<b>DALI</b>	T7GLA0750EXD	ø80mm	8W	750lm



\*IP rating below ceiling.


Material and Finish	
• Die cast aluminium heatsink	• Triac dimming as standard
• White bezel as standard	• Thermal cooling housing
• Interchangeable bezel	• Fire rated tested to Fr90 (90 minutes)
• Plug'n'Play driver	

## Dimensions



LED Characteristics			
CCT	3000°K	4000°K	5000°K
Board lumens	680 lm	750 lm	700 lm
Rated power	8W		
Ra (CRI)	>80		
Life expectancy@65°C	50,000 hrs L80 B10		

## Cut out



## Electrical Input

Rated input voltage	~230-240V AC
Rated input frequency	50-60Hz
Power factor	>0.9
Running current	0.04A
Total wattage	8W


## Weight



0.18kg

## Photometric Data

Calculation file	T7GLA0750WWEZ.ltd	T7GLA0750NWEZ.ltd	T7GLA0750CWEZ.ltd
LOR	99.98%	99.98%	99.98%
Luminaire lumens	625lm	762lm	713lm
Efficacy LL/CW	78.12	95.25	89.12



3-in-1	
3000°K	Warm White
4000°K	Neutral White
5000°K	Cool White